



**Lightweight,  
Micro Slim  
Scissor with  
True Slide-Out Deck**



# 1330SE

## Micro Scissor Lift

- 13 ft (4 m) Platform Height
- Fits On Most Elevators With Shortest Overall Length & Low GVW
- 24 in. (60 cm) Roll-Out Deck Extension with Incremental Lock Positions
- Direct Electric Drive For Exceptional Duty Cycle
- Retractable Pothole Protection
- Driveable At Full Height
- Fully Proportional Drive & Lift Controls
- Ultra Compact Design Fits Into Small And Tight Work Areas.
- Compact Size Without Compromising Generous Work Area



**Features**

**Work Area**

- Roll-out deck extension with incremental locking positions
- Standard swing gate
- Lanyard attachments (2)

**Performance**

- Direct electric drive
- Fully proportional drive and lift controls

**Power**

- 24v 85Ah DC electric power
- Battery charge indicator

**Serviceability**

- Lubrication-free scissor bearings
- Easy maintenance access to mechanical and electrical components in a slide-out tray

**Safety**

- Dedicated compartment protects electrical and hydraulic components
- Emergency shut-off at platform and lower controls
- Non-skid metal deck construction
- Descent alarm
- Drive speed interlock
- Multi-axis tilt sensor
- Scissor maintenance lock
- Automatic parking brake

**Other Features**

- Removable upper controls
- Voltage-compensating fully automatic battery charger
- Hour meter
- Machine tie downs
- Non-marking tires

**Optional Features**

- Flashing beacon (continuous)
- Inverter
- 2-Year extended warranty



**MEC Aerial Work Platforms**

1401 S. Madera Avenue  
 Kerman, CA 93630 | USA  
 Toll free: 1.877.MEC LIFT  
 1.877.632.5438  
 Tel: 559.842.1500  
 Fax: 559.842.1520  
 Email: info@MECawp.com | www.MECawp.com  
 97010



1330SE	U.S	Metric
<b>Heights</b>		
Working Height*	19 ft.*	6 m*
Platform Height	13 ft.	4 m
Stowed Height (Top Guardrail)	76 in.	1.9 m
Stowed Height (Platform Floor)	35 in.	0.9 m
Guardrail Height	39 in.	1.0 m
Toeboard Height	6 in.	15 cm
Ground Clearance (stowed)	2.5 in.	6 cm
Ground Clearance (elevated)	0.6 in.	1.5 cm
<b>Dimensions</b>		
Length - Stowed (Overall)	57 in.	1.45 m
Length - Stowed (Ladder Removed)	51 in.	1.3 m
Width	30 in	76 cm
Platform Length (Extended)	75 in.	1.9 m
Platform Length (Retracted)	51 in.	1.3 m
Roll-Out Deck Length	24 in.	0.6 m
Platform Width (Outside)	27.5 in.	0.7 m
Wheelbase	41 in.	1.0 m
Total Lift Capacity	530 lb	240 kg
Personnel Capacity	2	
Roll-Out Deck Capacity	250 lbs	113 kg
<b>Speed</b>		
Drive Speed (Stowed)	2.5 mph	4.0 km/h
Drive Speed (Elevated)	0.7 mph	1.1 km/h
<b>Performance</b>		
Gradeability	25%	
Turning Radius (Inside)	18 in.	45 cm
Weight (Approximately)	1,900 lbs.	860 kg
Power Source	24 v DC, 85Ah battery pack	
Controls	Proportional drive and lift controls	
Tires	9 in.	230 mm

\*Metric equivalent of working height adds 2m to platform height. U.S. adds 6 ft. to platform height. Weight may change with certain options or configurations.

**Important** - MEC scissor lifts must be on a firm level surface while elevated.

**Warranty** - MEC Aerial Work Platforms carry a one (1) year warranty on defective component parts and a five (5) year warranty on defective structural parts. This warranty applies to the original owner only. Consult your MEC dealer for warranty details.

Distributed by:

PSI = 112

Meets or exceeds the requirements of ANSI A92.6-2006.

Specifications subject to change without notice. Photos and diagrams in this brochure are for illustrative purposes only. Contact your MEC distributor for detailed instructions on the proper use and maintenance of this equipment.