



SCISSOR LIFT

MICRO SLIM ELECTRIC



Micro2032

Electric Scissor Lift

- Compact Size Almost 2 ft. (60 cm) Shorter Than Other 20 ft. (6 m) Lifts
- 800 lb. (363 kg) Capacity
- Dual Sheet Material Trays for up to 4 Sheets of Drywall
- Fixed Guardrails Under 79 in. (2 m) for Hassle-Free Transitions through Doorways
- AC Electric Drive for Extended Duty Cycle, Smoother Control and Faster Drive Speed
- Leak Containment System® Patent #11,112,060

Carry More Materials in Tight Work Areas with Micro Footprint



Standard Features

Work Area

Dual Sheet Material Trays - 110 lbs. (50 kg) per Side
Roll Out Deck Extension with Incremental Locking Positions
Standard Full Height Swing Gate
Lanyard Attachments (2)

Performance

800 lbs. (363 kg) Capacity
AC Electric Drive
Fully Proportional Drive and Lift Controls
Up To 25% Gradeability

Power

210Ah Maintenance-Free Batteries
Battery Charge Indicator

Serviceability

Lubrication-Free Scissor Bearings
Easy Maintenance Access to Mechanical and Electrical Components in Swing Out Trays
Parking Brake Release Switch for Towing

Safety

Lift Control Orientation Designed to Mitigate Entrapment
Dedicated Compartments Protect Electrical and Hydraulic Components
Emergency Shut-Off at Platform and Lower Controls
Non-Skid Metal Deck Construction
Descent Alarm
Drive Speed Interlock
Multi-Axis Tilt Sensor
Multiple Disk Brakes

Scissor Maintenance Lock
Automatic Parking Brakes
Automatic Pothole Protection

Other Features

Removable Upper Controls
Voltage-Compensating Fully Automatic Battery Charger
Hour Meter
Machine Tie Downs
Non-Marking Tires
All-Motion Alarm
Fork Lift Pockets
Flashing Beacon
Leak Containment System® (LCS)

Optional Features

Upper Control Box Supplementary Guard
900W Inverter
Tool Tray
Cold Weather Package
Pipe Rack
Second Year Extended Warranty



MEC Aerial Work Platforms

Tel: 559.842.1500 | 1401 S. Madera Avenue, Kerman, CA 93630 | USA
Toll free: 1.877.MEC LIFT | 1.877.632.5438 | Fax: 559.842.1520
Email: info@MECawp.com | www.MECawp.com

MEC® and Leak Containment System® are registered trademarks of California Manufacturing & Engineering Co., LLC. Leak Containment System® is Patent #11,112,060 97056 DTD 0524

Micro2032	U.S.	Metric
Heights		
Indoor Working Height*	25.7 ft.*	8 m*
Outdoor Working Height*	21 ft.*	6.6 m*
Indoor Platform Height	19.7 ft.	6 m
Outdoor Platform Height	15 ft.	4.6 m
Stowed Height (Top Guardrail)	78.7 in.	2 m
Stowed Height (Platform Floor)	35.4 in.	1.9 m
Guardrail Height	43.5 in	1.1 m
Toeboard Height	6 in.	0.15 m
Ground Clearance (Stowed)	3 in.	7.62 cm
Dimensions		
Length-Stowed (Overall)	74 in.	1.88 m
Length-Stowed (Ladder Removed)	68 in	1.73 m
Chassis Width	32.2 in	.82 m
Platform Length (Extended)	103.5 in.	2.63 m
Platform Length (Retracted)	68 in.	1.73 m
Roll-Out Deck Length	35.5 in.	.9 m
Platform Width (Outside)	29.1 in.	.74 m
Wheelbase	55 in.	1.4 m
Total Lift Capacity	800 lbs.	363 kg
Personnel Capacity	2 (Indoors); 1 (Outdoors)	
Roll-Out Deck Capacity	250 lbs.	113 kg
Speed		
Raise/Lower Speed	25/20 sec	
Drive Speed (Stowed)	3 mph	5 km/h
Drive Speed (Elevated)	.5 mph	.8 km/h
Performance		
Gradeability	25% 14 degrees	
Turning Radius (Inside)	6 in.	15 cm
Weight**	3,640 lbs.	1650 kg
Power Source	210Ah Maintenance-Free Batteries	
Controls	Proportional	
Tires	12 in. x 5 in	30 cm x 12.5 cm

*Metric equivalent of working height adds 2m to platform height. U.S. adds 6 ft. to platform height.

**Weight may vary with certain options or configurations.

Important - MEC scissor lifts must be on a hard level surface while elevated.

Warranty - MEC Aerial Work Platforms carry a one (1) year warranty on defective component parts and a five (5) year warranty on defective structural parts. This warranty applies to the original owner only. Consult your MEC dealer for warranty details.

Meets or exceeds the requirements of ANSI A92.20 and CSA B354.6 - 2017.

Specifications subject to change without notice. Photos and diagrams in this brochure are for illustrative purposes only. Contact your MEC distributor for detailed instructions on the proper use and maintenance of this equipment.

Distributed by: